

IM-DND-60 'Ci'

marine camera



High Resolution
Images

True Day/Night
Operation

Waterproof

Vandalproof
Construction

Subtle Design

Imaging Device: 1/3" Sony Super HAD CCD
Effective Picture Elements: 768x494 NTSC, 752x582 PAL
Horizontal Resolution: 480 TVL
Minimum Illumination: 0 Lux for Infrared Lighting Conditions
S/N Ratio: 45db
Auto Electronic Shutter: NTSC:1/60~1/100,000, PAL: 1/50~1/100,000
Iris Control: Auto
Gamma Characteristics: 0.45
Lens Options: Fixed: 2.9mm,3.6mm,4.3mm,6.0mm
AGC: Automatic
Sync System: Negative Sync, Internal
Video Output: 1Vp-p Composite Video/75 Ohms
Power Supply: DC 12V / 80mA
Operating Temperature: -20 degrees C to 50 degrees C
Dimensions: 60mm(W) x 57mm(D)
Weight: 320g

Iris Innovations Limited

Sailmakers Loft, Kings Copse Farm, Tanhouse Lane
Botley, Hampshire SO30 2SZ

Tel / Fax: +44 (0)2380 454484 - email:enquiries@iris-marine.com
www.iris-marine.com - www.scubar.co.uk